



PRODUCT DESCRIPTION

Stonkleen AS9 is a floor finish stripper/reliquifier designed to effectively remove aged, spray buffed and multiple layers of floor finish. Stonkleen AS9 easily removes even detergent resistant finishes. Stonkleen AS9 is formulated to require no agitation or scrubbing to remove floor finishes, reducing labor and equipment costs.

TYPICAL USES

Stonkleen AS9 is used for removal of floor finishes, especially Stonkleen AF2, from all types of floor surfaces. Stonkleen AS9 is safe for use on all Stonhard flooring systems.

PRODUCT ADVANTAGES

- Biodegradable
- Reliquifies old finish
- No scrubbing needed
- Saves on labor
- No ammonia odor
- Safe on most hard floor surfaces

PACKAGING

Stonkleen AS9 is a concentrated liquid and is available in 5 gallon pails. (FG# 8002A5)

STORAGE CONDITIONS

Store Stonkleen AS9 between 60-85°F/16-30°C. Keep from freezing.

DILUTION

Stonkleen AS9 is packaged in a concentrated, liquid form. Dilution can be accomplished with hot or cold water.

Light Wax Build-Up	1 part AS9 to 4 parts water
Medium Wax Build-Up	1 part AS9 to 3 parts water
Heavy Wax Build-Up	1 part AS9 to 2 parts water
Extra Heavy Wax Build-Up	1 part AS9 to 1 part water

APPLICATION

Apply diluted Stonkleen AS9 liberally to the floor. Allow the solution to stand for 5-10 minutes keeping the entire floor area wet. Do not allow to dry. Pick-up the solution with a squeegee equipped wet-vac. Rinse the floor with clear water. After the floor is dry, proceed with the application of a new finish.

Note: Stonkleen AS9 may also be used in a conventional stripping operation utilizing a floor machine equipped with a stripping pad at concentrations of 15 to 20 parts water to 1 part AS9.

RECOMMENDATIONS

- The dilution ratios stated are only approximations. Adjust your dilution ratio to optimize cleaning performance or to effect greater economy.

NOTES

- Material Safety Data Sheets on Stonkleen AS9 are available upon request.
- A staff of technical service engineers is available to answer questions related to our products in specific or flooring problems in general.
- Requests for technical service or literature can be made through local sales representatives and offices, or corporate offices located worldwide.

IMPORTANT:

Stonhard believes the information contained here to be true and accurate as of the date of publication. Stonhard makes no warranty, expressed or implied, based on this literature and assumes no responsibility for consequential or incidental damages in the use of the systems described, including any warranty of merchantability or fitness. Information contained here is for evaluation only. We further reserve the right to modify and change products or literature at any time and without prior notice.

3/08

Rev. 3/08



www.stonkleen.com



www.stonhard.com

Worldwide Offices:

USA	800-257-7953	Mexico	(52)-55-9140-4500	Europe	(32)-2-720-8982	Africa	(27)-11-254-5500
Canada	905-430-3333	South America	(54-3327)-44-2222	Middle East	(971)-4-3470460	Asia	(86)-21-5466-5118