



PRODUCT DESCRIPTION

Stonkleen AF2 is a durable, high-gloss, high speed buffable floor finish formulated for maximum performance in all types of environments. The unique blend of polymer and wax emulsions produces a long-wearing finish with a uniform gloss and texture.

USES/APPLICATIONS

Stonkleen AF2 is used to create a high-gloss finish or to restore the finish on any floor surface that requires resistance to soiling, staining, scuffing and black marking. Stonkleen AF2 provides excellent protection and gloss retention even in high traffic areas. Stonkleen AF2 can be used with all appropriate Stonhard floor systems.

PRODUCT ADVANTAGES

- High solids
- High speed buffable
- Extremely durable
- Detergent resistant
- Minimal coats required
- Anti-slip properties
- Variable strength/concentrated

PACKAGING

Stonkleen AF2 is available in ready-to-use, liquid form in 5 gallon pails.(FG# 8003A5)

STORAGE CONDITIONS

Store Stonkleen AF2 between 50 to 85° F/10 to 30° C. Keep from freezing.

COVERAGE

One gallon will cover approximately 1,000 to 1,500 sq. ft./93 to 140 sq. m.

PREPARATION

All surfaces must be clean and dry prior to application. Porous substrates should be sealed prior to applying Stonkleen AF2. Strip floor of old wax and finish with a stripper formulated to remove detergent resistant finishes. Stonkleen AS9 is recommended.

APPLICATION

1. Apply a thin, uniform coat of Stonkleen AF2 with a cotton yarn mop or a lamb's wool applicator. Allow to dry.
2. Once dry, polish/buff the surface using a Clark scrubber or a similar machine with a white buffing pad.
3. Repeat if necessary.

MAINTENANCE

Maintain the Stonkleen AF2 daily with a treated yarn dust mop to remove surface dirt. When necessary, clean with a damp mop or automatic scrubber-vac system and a neutral cleaner at the proper dilution. We recommend Stonkleen NC9 as a neutral cleaner to maintain floor finishes. Use spray buffing as needed. Worn areas can be recoated as needed.

NOTES

- Material Safety data Sheets for Stonkleen AF2 are available upon request.
- A staff of technical service engineers is available to assist with installation or to answer questions related to our products specifically, or flooring problems in general.
- Requests for technical service or literature can be made through local sales representatives and offices, or corporate offices located worldwide.

IMPORTANT:

Stonhard believes the information contained here to be true and accurate as of the date of publication. Stonhard makes no warranty, expressed or implied, based on this literature and assumes no responsibility for consequential or incidental damages in the use of the systems described, including any warranty of merchantability or fitness. Information contained here is for evaluation only. We further reserve the right to modify and change products or literature at any time and without prior notice.

3/08

Rev. 3/08



www.stonkleen.com



www.stonhard.com

Worldwide Offices:

USA	800-257-7953	Mexico	(52)-55-9140-4500	Europe	(32)-2-720-8982	Africa	(27)-11-254-5500
Canada	905-430-3333	South America	(54-3327)-44-2222	Middle East	(971)-4-3470460	Asia	(86)-21-5466-5118