# Safety Data Sheet

# Prepared in Accordance with HCS 29 C.F.R. 1910.1200



# 1. Identification of the Substance/Mixture and the Company/Undertaking

1.1	Product Identifier	56658/B	Revision Date:	03/13/2024
	Product Name:	Stonchem 600 Series Broadcast Gray Resin	Supersedes Date:	01/06/2023
1.2	Relevant identified uses of the substance or mixture and uses advised against	Component of multicomponent industrial coatings - Industrial use. For use by appropriately trained applicators. Please see Technical Data Sheet. Advised aga others than recommended		

## 1.3 Details of the supplier of the safety data sheet

Manufacturer:	Stonhard, Division of StonCor Group, Inc. 1000 East Park Avenue
	Maple Shade, NJ 08052

+1 856 7797500 (US)

ehs@stonhard.com

Datasheet Produced by:

1.4 Emergency telephone number:

+1 703-741-5970 - North America +1 800-424-9300 +55 11 4349 1359 - South America +52 55 8526 4930 - Central America +44 20 3885 0382 - Middle East, Eastern Europe, Western Europe, and Africa +65 3163 8374 - Asia, South Asia, And Oceania

# 2. Hazard Identification

## 2.1 Classification of the substance or mixture

Acute Toxicity, Inhalation, category 4 Hazardous to the aquatic environment, Chronic, category 2 Carcinogenicity, category 1A Eye Irritation, category 2A Germ Cell Mutagenicity, category 2 Skin Irritation, category 2 Skin Sensitizer, category 1 STOT, repeated exposure, category 2 STOT, single exposure, category 2 STOT, single exposure, category 3, RTI

## 2.2 Label elements

Symbol(s) of Product



## Signal Word

Danger

### Named Chemicals on Label

Butyl glycidyl ether, mica, quartz (silicon dioxide), PHENOL, 4,4'-(1-METHYLETHYLIDENE) BIS-, POLYMER WITH (CHLOROMETHYL) OXIRANE, phenol, polymer with formaldehyde, glycidyl ether

## HAZARD STATEMENTS

Skin Irritation, category 2	H315	Causes skin irritation.
Skin Sensitizer, category 1	H317	May cause an allergic skin reaction.
Eye Irritation, category 2A	H319	Causes serious eye irritation.
Acute Toxicity, Inhalation, category 4	H332	Harmful if inhaled.
STOT, single exposure, category 3, RTI	H335	May cause respiratory irritation.
Germ Cell Mutagenicity, category 2	H341	Suspected of causing genetic defects.
Carcinogenicity, category 1A	H350-1A	May cause cancer.
STOT, single exposure, category 2	H371	May cause damage to organs.
STOT, repeated exposure, category 2	H373	May cause damage to organs through prolonged or repeated exposure.
Hazardous to the aquatic environment, Chronic, category 2	H411	Toxic to aquatic life with long lasting effects.
PRECAUTION PHRASES		
	P201	Obtain special instructions before use.
	P202	Do not handle until all safety precautions have been read and understood.
	P260	Do not breathe dust/fume/gas/mist/vapours/spray.
	P264	Wash hands thoroughly after handling.
	P273	Avoid release to the environment.
	P280	Wear protective gloves/protective clothing/eye protection/ face protection.
	P284	Wear respiratory protection.
	P302+352	IF ON SKIN: Wash with plenty of soap and water.
	P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
	P305+351+338	· · ·

P308+313 P308+P313 P309+P311 P314 P333+313	<ul> <li>IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.</li> <li>IF exposed or concerned: Get medical advice/attention.</li> <li>IF exposed or concerned: Get medical advice/attention</li> <li>IF exposed or if you feel unwell: Call a POISON CENTER or doctor/physician.</li> <li>Get medical advice/attention if you feel unwell.</li> <li>If skin irritation or rash occurs: Get medical advice/attention.</li> </ul>
P391	Collect spillage.
P405	Store locked up.

# 2.3 Other hazards

No Information

## Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

3.2 Mixtures					
Hazardous ingredients					
Name According to EEC	EINEC No.	CAS-No.	<u>%</u>	<b>Classifications</b>	
phenol, polymer with formaldehyde, glycidyl ether	608-164-0	28064-14-4	50 - <75	H315-317-319-411	Aquatic Chronic 2, Eye Irrit. 2, Skin Irrit. 2, Skin Sens. 1
mica	601-648-2	12001-26-2	10 - <25	H319-335	Eye Irrit. 2, STOT SE 3 RTI
Butyl glycidyl ether	219-376-4	2426-08-6	2.5 - <10	H226-302-317-332-3 35-341-351-412	Acute Tox. 4 Inhalation, Acute Tox. 4 Oral, Aquatic Chronic 3, Carc. 2, Flam. Liq. 3, Muta. 2, Skin Sens. 1 STOT SE 3 RTI
quartz (silicon dioxide)	238-878-4	14808-60-7	2.5 - <10	H350-370	Carc. 1A, STOT SE 1
titanium dioxide	236-675-5	13463-67-7	2.5 - <10	H351	Carc. 2
PHENOL, 4,4'-(1- METHYLETHYLIDENE) BIS-, POLYMER WITH (CHLOROMETHYL) CHLOROMETHYL) OXIRANE	500-033-5	25068-38-6	1.0 - <2.5	H315-317-319-335-4 11	Aquatic Chronic 2, Eye Irrit. 2, Skin Irrit. 2, Skin Sens. 1, STOT SE 3 RTI
hydrated, amorphous silica		112926-00-8	1.0 - <2.5		

CAS-No.

M-Factors

28064-14-4 12001-26-2 2426-08-6 14808-60-7 13463-67-7 25068-38-6 112926-00-8

Additional Information:

The text for GHS Hazard Statements shown above (if any) is given in Section 16.

## 4. First-aid Measures

### 4.1 Description of First Aid Measures

GENERAL NOTES: When symptoms persist or in all cases of doubt seek medical advice.

AFTER INHALATION: Move to fresh air. Consult a physician after significant exposure.

AFTER SKIN CONTACT: Use a mild soap if available. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.

AFTER EYE CONTACT: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses. If eye irritation persists, consult a specialist.

**AFTER INGESTION:** Gently wipe or rinse the inside of the mouth with water. Give small amounts of water to drink. Do NOT induce vomiting. Never give anything by mouth to an unconscious person.

### Self protection of the first aider:

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

### 4.2 Most important symptoms and effects, both acute and delayed

Irritating to skin. May cause sensitization by skin contact. Harmful to aquatic organisms.

#### 4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

## 5. Fire-fighting Measures

### 5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam

FOR SAFETY REASONS NOT TO BE USED: Alcohol, Alcohol based solutions, any other media not listed above.

## 5.2 Special hazards arising from the substance or mixture

No Information

## 5.3 Advice for firefighters

In the event of fire, wear self-contained breathing apparatus. High volume water jet. Hazardous decomposition products formed under fire conditions. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide. Contains epoxy constituents. See information supplied by the manufacturer.

## 6. Accidental Release Measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment.

### 6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains. May cause long-term adverse effects in the aquatic environment.

### 6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

## 6.4 Reference to other sections

Please refer to disposal requirements or country specific disposal requirements for this material. See Section 8 and 13 for further information.

## 7. Handling and Storage

### 7.1 Precautions for safe handling

**INSTRUCTIONS FOR SAFE HANDLING:** Use only in area provided with appropriate exhaust ventilation. Wear personal

protective equipment.

**PROTECTION AND HYGIENE MEASURES:** Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

### 7.2 Conditions for safe storage, including any incompatibilities

**CONDITIONS TO AVOID:** Extremes of temperature and direct sunlight.

**STORAGE CONDITIONS:** Store in original container. Keep locked up or in an area accessible only to qualified or authorised persons. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

## 7.3 Specific end use(s)

The mixing and application to be in accordance with the technical data sheets.

# 8. Exposure Controls/Personal Protection

## 8.1 Control parameters

#### Ingredients with Occupational Exposure Limits

(US)

Name	CAS-No.	ACGIH TWA	ACGIH STEL	ACGIH Ceiling
phenol, polymer with formaldehyde, glycidyl ether	28064-14-4			
mica	12001-26-2	3 MGM3		
Butyl glycidyl ether	2426-08-6	3 PPM		
quartz (silicon dioxide)	14808-60-7	0.025 MGM3		
titanium dioxide	13463-67-7	10 MGM3 10 MGM3		
PHENOL, 4,4'-(1- METHYLETHYLIDENE) BIS-, POLYMER WITH (CHLOROMETHYL OXIRANE	25068-38-6 .)			
hydrated, amorphous silica	112926-00-8	10.00 MG/M3		
Name	<u>CAS-No.</u>	<u>OSHA PEL</u>	OSHA STEL	
Name phenol, polymer with formaldehyde, glycidyl ether	<u>CAS-No.</u> 28064-14-4	<u>OSHA PEL</u>	<u>OSHA STEL</u>	
phenol, polymer with formaldehyde,		OSHA PEL 3 mg/m3	<u>OSHA STEL</u>	
phenol, polymer with formaldehyde, glycidyl ether	28064-14-4 12001-26-2		<u>OSHA STEL</u>	
phenol, polymer with formaldehyde, glycidyl ether mica	28064-14-4 12001-26-2	3 mg/m3	<u>OSHA STEL</u>	
phenol, polymer with formaldehyde, glycidyl ether mica Butyl glycidyl ether	28064-14-4 12001-26-2 2426-08-6	3 mg/m3 135 MGM3, 25 PPM	<u>OSHA STEL</u>	
phenol, polymer with formaldehyde, glycidyl ether mica Butyl glycidyl ether quartz (silicon dioxide)	28064-14-4 12001-26-2 2426-08-6 14808-60-7 13463-67-7 25068-38-6	3 mg/m3 135 MGM3, 25 PPM 0.05 MGM3	<u>OSHA STEL</u>	

FURTHER INFORMATION: Refer to the regulatory exposure limits for the workforce enforced in each country.

#### 8.2 Exposure controls

#### Personal Protection RESPIRATORY PROTECTION: No personal respiratory protective equipment normally required.

## EYE PROTECTION: Safety glasses.

HAND PROTECTION: Impervious gloves. Long sleeved clothing. Remove and wash contaminated clothing before re-use. OTHER PROTECTIVE EQUIPMENT: No Information

**ENGINEERING CONTROLS:** Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas.

# 9. Physical and Chemical Properties

9.1	Information on basic physical and chemical properties Appearance:	Not determined
	Physical State	Liquid
	Odor	SLIGHT AROMATIC ODOR
	Odor threshold	Not determined
	рН	N/A
	Melting point / freezing point (°C)	Not determined
	Boiling point/range (°C)	101 - N.D.
	Flash Point, (°F / °C)	170F / 77C
	Evaporation rate	Not determined
	Flammability (solid, gas)	Not determined
	Upper/lower flammability or explosive limits	N/A - N/A
	Vapour Pressure	N/A
	Vapour density	N/A
	Relative density	Not determined
	Solubility in / Miscibility with water	INSOLUBLE
	Partition coefficient: n-octanol/water	Not determined
	Auto-ignition temperature (°C)	Not determined
	Decomposition temperature (°C)	Not determined
	Viscosity	N/A
	Explosive properties	Not determined
	Oxidising properties	Not determined
9.2	Other information VOC Content g/l: Grams of VOC per liter of coating product as applied (r Specific Gravity (g/cm3)	20 nixture of Part A and Part B) per ASTM D2369 Method E. 1.342

# 10. Stability and Reactivity

### 10.1 Reactivity

No reactivity hazards known under normal storage and use conditions.

### 10.2 Chemical stability

No decomposition if stored and applied as directed. Stable under normal conditions.

## 10.3 Possibility of hazardous reactions

Hazardous polymerisation does not occur.

#### 10.4 Conditions to avoid

Extremes of temperature and direct sunlight.

## 10.5 Incompatible materials

Strong oxidizing agents. Acids and bases.

#### 10.6 Hazardous decomposition products

Thermal decomposition can lead to release of irritating gases and vapours. Alcohols. Exothermic reaction. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), dense black smoke.

## 11. Toxicological Information

#### 11.1 Information on toxicological effects

Acute Toxicity: Oral LD50: No information Inhalation LC50: No information No information available. Irritation: No information available. Corrosivity: Sensitization: No information available. No information available. Repeated dose toxicity: Carcinogenicity: No information available. **Mutagenicity:** No information available. No information available. Toxicity for reproduction: No information available. STOT-single exposure: No information available. STOT-repeated exposure: No information available. Aspiration hazard:

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	Chemical Name	Oral LD50	Dermal LD50	Vapor LC50	Gas LC50	Dust/Mist LC50
28064-14-4	phenol, polymer with formaldehyde, glycidyl ether	5000 mg/kg. oral, rat	>2000 mg/kg, rabbit		0.000	0.000
12001-26-2	mica	>16000 mg/kg			0.000	0.000
14808-60-7	quartz (silicon dioxide)	>2000 mg/kg			0.000	0.000
13463-67-7	titanium dioxide	10000 mg/kg, oral (rat)			0.000	6,82 mg/l (rat) 4h
25068-38-6	PHENOL, 4,4'-(1- METHYLETHYLIDENE) BIS-, POLYMER WITH (CHLOROMETHYL) OXIRANE	>2000 mg/kg, rat, oral	>2000 mg/kg, rat		0.000	0.000

## Additional Information:

This product is classified as a "Reproductive Toxicity - Category 2" due to containing a substance classified as a reproductive toxin via ingestion / oral exposure route only. Normal product application methods by trained crew members would not present a risk of oral exposure or ingestion. Constituents of this product may include crystalline silica which, if inhalable, may cause silicosis, a form or progressive pulmonary fibrosis. Inhalable crystalline silica is listed by IARC as a group 1 carcinogen (lung) based on sufficient evidence in occupationally exposed humans and sufficient evidence in animals. Crystalline silica is also listed by the NTP as a known human carcinogen. This classification is relevant when exposed to Quartz (silicon dioxide) in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities. Constituents may also include abestiform or non-asbestiform tremolite or other serious lung problems. This product may contain Quartz (silicon dioxide), which is listed by IARC as a known carcinogenic or cause other serious lung problems. This product may contain Quartz (silicon dioxide), which is listed by IARC as a known carcinogenic to humans (Group 1). This classification is relevant when exposed to Quartz (silicon dioxide) in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities. This product may contain Titanium Dioxide, which is listed by IARC as possibly carcinogenic to humans (Group 2B). This classification is relevant when exposed to titanium dioxide in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities. This product may contain Titanium Dioxide, which is listed by IARC as possibly carcinogenic to humans (Group 2B). This classification is relevant when exposed to titanium dioxide in dust or powder form only, including cured product that is subject to san

# 12. Ecological Information

12.1	Toxici	ty:				
	EC!	50 48hr (Daphnia):		ormation		
	IC5	0 72hr (Algae):	No inf	ormation		
	LCS	50 96hr (fish):	No inf	ormation		
12.2	Persis	tence and degradability:	No inf	ormation		
12.3	Bioaco	cumulative potential:	No inf	ormation		
12.4	Mobili	ty in soil:	No inf	ormation		
12.5	Result asses	ts of PBT and vPvB sment:	The pr	oduct does not meet the	e criteria for PBT/VP	vB in accordance with Annex XIII.
12.6	Other	adverse effects:	No inf	ormation		
<u>CAS-</u>	<u>No.</u>	Chemical Name		<u>EC50 48hr</u>	<u>IC50 72hr</u>	<u>LC50 96hr</u>
28064	4-14-4	phenol, polymer with formaldehyde, gl ether	ycidyl	No information	No information	
1200	1-26-2	mica		No information	No information	
2426-	-08-6	Butyl glycidyl ether		No information	No information	
1480	8-60-7	quartz (silicon dioxide)		No information	No information	
1346	3-67-7	titanium dioxide		>100 mg/l (EC50, 48h, Daphnia magna OECD202)ation	No information	>1000 mg/l
2506	8-38-6	PHENOL, 4,4'-(1-METHYLETHYLIDE BIS-, POLYMER WITH (CHLOROMET OXIRANE		1.8 mg/l	No information	1.3 mg/L
11292	26-00-8	hydrated, amorphous silica		No information	No information	
13.	Disp	osal Considerations				

**13.1 WASTE TREATMENT METHODS:** If recycling is not practicable, dispose of in compliance with local regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal.

## 14. Transport Information

14.1	UN number	N/A
14.2	UN proper shipping name	Not Regulated
	Technical name	Not applicable
14.3	Transport hazard class(es)	N/A
	Subsidiary shipping hazard	Not applicable
14.4	Packing group	Not applicable
14.5	Environmental hazards	Not applicable
14.6	Special precautions for user	Not applicable
	EmS-No.:	N/A
14.7	Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code	Not applicable

## 15. Regulatory Information

<sup>15.1</sup> Safety, health and environmental regulations/legislation for the substance or mixture:

# U.S. Federal Regulations: As follows -

### **CERCLA - Sara Hazard Category**

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Carcinogenicity, Acute Toxicity (any route of exposure), Skin Corrosion or Irritation, Respiratory or Skin Sensitization, Serious eye damage or eye irritation, Specific target organ toxicity (single or repeated exposure), Germ cell mutagenicity

### Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the U.S. Superfund Amendment and Reauthorization Act (SARA) of 1986 and 40 CFR part 372:

Chemical Name

CAS-No.

<u>%</u>

No SARA 313 substances exist in this product above de minimis concentrations.

### Toxic Substances Control Act:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA 12(b) components exist in this product.

## U.S. Clean Air Act:

EPA Coating Category:	INDUSTRIAL MAINTENANCE COATINGS
EPA VOC Content Limit (g/l):	450
Product VOC Content (g/l)	20
Thinning Recommendations:	NONE
Application Recommendations:	FOR INDUSTRIAL USE ONLY

\* As per the federal EPA definition for coating categories in 40 CFR 59.401.

\*\* Grams of VOC per liter of coating product as applied (mixture of Part A and Part B) per ASTM D2369 Method E.

# U.S. State Regulations: As follows -

## New Jersey Right-to-Know:

The following materials are non-hazardous, but are among the top five components in this product.

## Chemical Name

No NJ Right-To-Know components exist in this product.

## Pennsylvania Right-To-Know

The following non-hazardous ingredients are present in the product at greater than 3%.

No PA Right-To-Know components exist in this product.

## California Proposition 65:

WARNING: Cancer - www.P65Warnings.ca.gov

WARNING: Reproductive Toxicant -- www.P65Warnings.ca.gov

# International Regulations: As follows -

### \* Canadian DSL:

All chemical ingredients included on inventory or exempt.

### 15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

# 16. Other Information

### Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H226Flammable liquid and vapour.H302Harmful if swallowed.H315Causes skin irritation.H317May cause an allergic skin reaction.

CAS-No.

H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H341	Suspected of causing genetic defects.
H350	May cause cancer.
H351	Suspected of causing cancer.
H370	Causes damage to organs.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

#### **Reasons for revision**

Substance and/or Product Properties Changed in Section(s): 02 - Hazard Identification 03 - Composition/Information On Ingredients 09 - Physical and Chemical Properties 11 - Toxicological Information 15 - Regulatory Information Substance Chemical Name Changed Revision Statement(s) Changed

List of References:

This Safety Data Sheet was compiled with data and information from the following sources:

- The Ariel Regulatory Database provided by the 3E Corporation in Copenhagen, Denmark.

- Joint Research Centre in Ispra, Italy.
- Regulation (EC) 1272/2008 with subsequent amendments.
- Regulation (EC) 1272/2006 with subsequent amendments.
- Commission Regulation (EU) 2020/878
- EU Council Decision 2000/532/EC and its Annex entitled "List of Wastes"
- Safety Data Sheet from raw material supplier
- The classification declared in sec. 2.2 is based on the calculation methods set out in Annex I and Annex II of the CLP Reg. 1272/2008 on the composition of the formula.

Acronym & Abbreviation Key:

CLP	Classification, Labeling & Packaging Regulation
EC	European Commission
EU	European Union
US	United States
CAS	Chemical Abstract Service
EINECS	European Inventory of Existing Chemical Substances
REACH	Registration, Evaluation, Authorization of Chemicals Regulation
GHS	Globally Harmonized System of Classification and Labeling of Chemicals
LTEL	Long term exposure limit
STEL	Short term exposure limit
OEL	Occupational exposure limit
ppm	Parts per million
mg/m3	Milligrams per cubic meter
TLV	Threshold Limit Value
ACGIH	American Conference of Governmental Industrial Hygienists
OSHA	Occupational Safety & Health Administration
PEL	Permissible Exposure Limits
VOC	Volatile organic compounds
g/l	Grams per liter
mg/kg	Milligrams per kilogram
N/A	Not applicable
LD50	Lethal dose at 50%
LC50	Lethal concentration at 50%
EC50	Half maximal effective concentration

#### Date Printed: 03/19/2024

IC50	Half maximal inhibitory concentration
PBT	Persistent bioaccumulative toxic chemical
vPvB	Very persistent and very bioaccumulative
EEC	European Economic Community
ADR	International Transport of Dangerous Goods by Road
RID	International Transport of Dangerous Goods by Rail
UN	United Nations
IMDG	International Maritime Dangerous Goods Code
IATA	International Air Transport Association
MARPOL	International Convention for the Prevention of Pollution From Ships, 1973 as
	modified by the Protocol of 1978
IBC	International Bulk Container
RTI	Respiratory Tract Irritation
NE	Narcotic Effects
IMO	International Maritime Organization
Note P:	The classification as a carcinogen or mutagen need not apply; the substance
	contains less than 0,1 % w/w benzene
Note 10:	The classification as a carcinogen by inhalation applies only to mixtures in
	powder form containing 1 $\%$ or more of titanium dioxide which is in the form of
	or incorporated in particles with aerodynamic diameter $\leq$ 10 µm.

For further information, please contact: Technical Services Department

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product or where instructions and recommendations are not followed.