Safety Data Sheet Prepared in Accordance with HCS 29 C.F.R. 1910.1200



1. Identification of the Substance/Mixture and the Company/Undertaking

55701B **Revision Date: Product Identifier** 12/23/2022

Supersedes Date: 08/29/2020 Stonchem 700 Basecoat Gray **Product Name:**

Resin

Relevant identified uses of the

substance or mixture and uses

advised against

Base component of 2 components coating - Industrial use. For use by appropriately trained applicators. Please see Technical Data Sheet. Advised against: others than

recommended

1.3 Details of the supplier of the safety data sheet

> Stonhard, Division of StonCor Group, Inc. Manufacturer:

1000 East Park Avenue Maple Shade, NJ 08052

+1 856 7797500 (US)

ehs@stonhard.com **Datasheet Produced by:**

1.4 Emergency telephone number: CHEMTREC 1-800-424-9300 (Inside US)

CHEMTREC +1 703 5273887 (Outside US)

Giftinformasjonen: +47 22 59 13 00

2. Hazard Identification

2.1 Classification of the substance or mixture

Acute Toxicity, Inhalation, category 4 Carcinogenicity, category 1A Eye Irritation, category 2A Flammable Liquid, category 3 Germ Cell Mutagenicity, category 1B Reproductive_ToxicityD_category_2 STOT, single exposure, category 1 Skin Irritation, category 2

2.2 Label elements

Symbol(s) of Product



Signal Word

Danger

Named Chemicals on Label

Styrene, quartz (silicon dioxide), Solvent naphtha (petroleum), light arom.

HAZARD STATEMENTS

Flammable Liquid, category 3 Skin Irritation, category 2 Eye Irritation, category 2A Acute Toxicity, Inhalation, category 4 Germ Cell Mutagenicity, category 1B Carcinogenicity, category 1A Reproductive_ToxicityD_category_2 STOT, single exposure, category 1 PRECAUTION PHRASES	H226 H315 H319 H332 H340-1B H350-1A H361d H370	Flammable liquid and vapour. Causes skin irritation. Causes serious eye irritation. Harmful if inhaled. May cause genetic defects. May cause cancer. Suspected of damaging the unborn child. Causes damage to organs.
	P201	Obtain special instructions before use.
	P202	Do not handle until all safety precautions have been read and understood.
	P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
	P260	Do not breathe dust/fume/gas/mist/vapours/spray.
	P264	Wash hands thoroughly after handling.
	P280	Wear protective gloves/protective clothing/eye protection/ face protection.
	P284	Wear respiratory protection.
	P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
	P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.
	P307+311	IF exposed, call a POISON CENTER or doctor/physician.
	P308+313	IF exposed or concerned: Get medical advice/attention.
	P314	Get medical advice/attention if you feel unwell.
	P332+313 P403+233	If skin irritation occurs: Get medical advice/attention. Store in a well-ventilated place. Keep container tightly closed.

2.3 Other hazards

No Information

Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

3. Composition/Information On Ingredients

3.2 Mixtures

Hazardous ingredients

Name According to EEC polyester resin	EINEC No.	CAS-No. 18275200000-50 45	<u>%</u> 25 - <50	Classifications	
Styrene	202-851-5	100-42-5	10 - <25	H226-304-315-319-3 32-335-361d-372	Acute Tox. 4 Inhalation, Asp. Tox. 1, Eye Irrit. 2, Flam. Liq. 3, Repr. 2, Skin Irrit. 2, STOT RE 1, STOT SE 3 RTI
quartz (silicon dioxide)	238-878-4	14808-60-7	10 - <25	H350-370	Carc. 1A, STOT SE 1
titanium dioxide	236-675-5	13463-67-7	1.0 - <2.5	H351	Carc. 2
Solvent naphtha (petroleum), light arom.	265-199-0	64742-95-6	0.1 - <1.0	H304-332-335-336-3 40-350	Acute Tox. 4 Inhalation, Asp. Tox. 1, Carc. 1B, Muta. 1B, STOT SE 3 NE, STOT SE 3 RTI

CAS-No.	M-Factors
18275200000-5045	0
100-42-5	0
14808-60-7	0
13463-67-7	0
64742-95-6	0

Additional Information: The text for GHS Hazard Statements shown above (if any) is given in Section 16.

4. First-aid Measures

4.1 Description of First Aid Measures

GENERAL NOTES: When symptoms persist or in all cases of doubt seek medical advice.

AFTER INHALATION: Move to fresh air. Consult a physician after significant exposure.

AFTER SKIN CONTACT: Use a mild soap if available. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.

AFTER EYE CONTACT: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses.

AFTER INGESTION: Gently wipe or rinse the inside of the mouth with water. Give small amounts of water to drink. Do NOT induce vomiting. Never give anything by mouth to an unconscious person.

Self protection of the first aider:

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Harmful by inhalation. Irritating to eyes. Harmful in contact with skin and if swallowed.

4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

5. Fire-fighting Measures

5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam

FOR SAFETY REASONS NOT TO BE USED: Alcohol, Alcohol based solutions, any other media not listed above.

5.2 Special hazards arising from the substance or mixture

Flammable.

5.3 Advice for firefighters

Flash back possible over considerable distance. In the event of fire, wear self-contained breathing apparatus. Do not use a solid water stream as it may scatter and spread fire. Hazardous decomposition products formed under fire conditions. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment. Remove all sources of ignition.

6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains.

6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

Please refer to disposal requirements or country specific disposal requirements for this material. See Section 8 and 13 for further information.

7. Handling and Storage

7.1 Precautions for safe handling

INSTRUCTIONS FOR SAFE HANDLING: Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Vapours may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Electrical equipment should be protected to the appropriate standard. Preparation may charge electrostatically: always use earthing leads when transferring from one container to another. Use only in area provided with appropriate exhaust ventilation. To avoid ignition of vapours by static electricity discharge, all metal parts of the equipment must be grounded. Wear personal protective equipment. Do not breathe vapours or spray mist. Use only explosion-proof equipment. Keep away from sources of ignition - No smoking.

PROTECTION AND HYGIENE MEASURES: Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

7.2 Conditions for safe storage, including any incompatibilities

CONDITIONS TO AVOID: Direct sources of heat.

STORAGE CONDITIONS: Store in original container. Keep locked up or in an area accessible only to qualified or authorised persons. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

7.3 Specific end use(s)

The mixing and application to be in accordance with the technical data sheets.

8. Exposure Controls/Personal Protection

8.1 Control parameters

Ingredients with Occupational Exposure Limits

(US)

<u>Name</u>	CAS-No.	ACGIH TWA	ACGIH STEL	ACGIH Ceiling
polyester resin	18275200000-	5.0 MG/M3		
Styrene	100-42-5	10 PPM	20 PPM	

14808-60-7 0.025 MGM3 quartz (silicon dioxide)

13463-67-7 10 MGM3 10 MGM3 titanium dioxide

300.0 PPM Solvent naphtha (petroleum), light arom. 64742-95-6

Name CAS-No. OSHA PEL **OSHA STEL**

18275200000-5.0 MG/M3 polyester resin

100-42-5 215 MGM3, 50 PPM 425 MGM3, 100 PPM Styrene

0.05 MGM3 quartz (silicon dioxide) 14808-60-7

15 MGM3 titanium dioxide 13463-67-7

500.0 PPM Solvent naphtha (petroleum), light arom. 64742-95-6

FURTHER INFORMATION: Refer to the regulatory exposure limits for the workforce enforced in each country.

8.2 Exposure controls

Personal Protection

RESPIRATORY PROTECTION: Respirator with filter for organic vapor.

EYE PROTECTION: Ensure that eyewash stations and safety showers are close to the workstation location. Safety glasses. Safety goggles.

HAND PROTECTION: Impervious gloves. Long sleeved clothing. Remove and wash contaminated clothing before re-use.

OTHER PROTECTIVE EQUIPMENT: No Information

ENGINEERING CONTROLS: Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas.

56 - N.D.

9. Physical and Chemical Properties

9.1 Information on basic physical and chemical properties

Appearance: **GRAY**

Physical State LIQUID

Odor Solvent like

Odor threshold Not determined

pΗ Non-aqueous

Melting point / freezing point (°C) Not determined Boiling point/range (°C)

Flash Point, (°F / °C) 73F / 23C

Evaporation rate Not determined

Flammability (solid, gas) Not determined

Upper/lower flammability or explosive Not determined - Not determined

limits

Vapour Pressure Not determined Vapour density Not determined Relative density Not determined

Solubility in / Miscibility with water NIL

Partition coefficient: n-octanol/water Not determined

Auto-ignition temperature (°C)

Not determined

Decomposition temperature (°C)

Not determined

Viscosity 16600 CPS
Explosive properties Not determined

Oxidising properties

Not applicable

9.2 Other information

VOC Content g/l:

Grams of VOC per liter of coating product as applied (mixture of Part A and Part B) per ASTM D2369 Method E.

Specific Gravity (g/cm3) 1.563

10. Stability and Reactivity

10.1 Reactivity

No reactivity hazards known under normal storage and use conditions.

10.2 Chemical stability

Stable under recommended storage conditions. Risk of ignition.

10.3 Possibility of hazardous reactions

Hazardous polymerisation does not occur.

10.4 Conditions to avoid

Direct sources of heat.

10.5 Incompatible materials

Strong oxidizing agents.

10.6 Hazardous decomposition products

Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), dense black smoke.

11. Toxicological Information

11.1 Information on toxicological effects

Acute Toxicity:

Oral LD50: No information Inhalation LC50: No information

Irritation: No information available.

Corrosivity: No information available.

Sensitization: No information available.

Repeated dose toxicity: No information available.

Carcinogenicity: No information available.

Mutagenicity: No information available.

Toxicity for reproduction: No information available.

STOT-single exposure: No information available.

STOT-repeated exposure: No information available.

Aspiration hazard: No information available.

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	<u>Chemical Name</u>	Oral LD50	Dermal LD50	Vapor LC50	Gas LC50	Dust/Mist LC50
100-42-5	Styrene	2650 mg/kg	>2000 mg/kg	2770 ppm, 4 h	0.000	0.000
14808-60-7	quartz (silicon dioxide)	>2000 mg/kg			0.000	0.000
13463-67-7	titanium dioxide	10000 mg/kg, oral (rat)			0.000	6,82 mg/l (rat) 4h
64742-95-6	Solvent naphtha (petroleum), light arom.	4700 mg/kg, oral, rat	>3480 mg/kg, rabbit	3670 ppm/4 hours, rat, inhalation	3670 ppm, rat, 4hrs	0.000

Additional Information:

Constituents of this product may include crystalline silica which, if inhalable, may cause silicosis, a form or progressive pulmonary fibrosis. Inhalable crystalline silica is listed by IARC as a group 1 carcinogen (lung) based on sufficient evidence in occupationally exposed humans and sufficient evidence in animals. Crystalline silica is also listed by the NTP as a known human carcinogen. This classification is relevant when exposed to Quartz (silicon dioxide) in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities. Constituents may also include abestiform or non-asbestiform tremolite or other silicates as impurities, and above dei minimus exposure to these impurities in inhalable form may be carcinogenic or cause other serious lung problems. This product may contain Quartz (silicon dioxide), which is listed by IARC as a known carcinogenic to humans (Group 1). This classification is relevant when exposed to Quartz (silicon dioxide) in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities. This product may contain Titanium Dioxide, which is listed by IARC as possibly carcinogenic to humans (Group 2B). This listing is based on inadequate evidence of carcinogenicity in humans and sufficient evidence in experimental animals. This classification is relevant when exposed to titanium dioxide in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities.

12. Ecological Information

12.1 Toxicity:

EC50 48hr (Daphnia): No information No information IC50 72hr (Algae): No information LC50 96hr (fish):

12.2 Persistence and degradability: No information

12.3 Bioaccumulative potential: No information

12.4 Mobility in soil: No information

12.5 Results of PBT and vPvB The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

assessment:

12.6 Other adverse effects: No information

CAS-No.	Chemical Name	EC50 48hr	IC50 72hr	LC50 96hr
18275200000 5045)-polyester resin	No information	No information	
100-42-5	Styrene	4.7 mg/l	No information	4.02 mg/l
14808-60-7	quartz (silicon dioxide)	No information	No information	
13463-67-7	titanium dioxide	>100 mg/l (EC50, 48h, Daphnia magna OECD202)ation	No information	>1000 mg/l
64742-95-6	Solvent naphtha (petroleum), light arom.	>1 - 10 mg/l	>1 - 10 mg/l	>10-100 mg/l

13. Disposal Considerations

WASTE TREATMENT METHODS: Do not burn, or use a cutting torch on, the empty drum. If recycling is not practicable, dispose of in compliance with local regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport Information

UN3269 14.1 UN number

14.2 UN proper shipping name Polyester Resin Kit Not applicable **Technical name**

14.3 Transport hazard class(es)

Subsidiary shipping hazard Not applicable

14.4 Packing group

Not applicable 14.5 Environmental hazards 14.6 Special precautions for user Not applicable EmS-No.: F-E, S-D

14.7 Transport in bulk according to Annex II of

MARPOL 73/78 and the IBC code

Not applicable

15. Regulatory Information

Safety, health and environmental regulations/legislation for the substance or mixture:

U.S. Federal Regulations: As follows -

CERCLA - Sara Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Flammable (gases, aerosols, liquids, or solids), Carcinogenicity, Acute Toxicity (any route of exposure), Reproductive toxicity, Skin Corrosion or Irritation, Serious eye damage or eye irritation, Specific target organ toxicity (single or repeated exposure), Germ cell mutagenicity

Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the U.S. Superfund Amendment and Reauthorization Act (SARA) of 1986 and 40 CFR part 372:

<u>Chemical Name</u> <u>CAS-No.</u> %

Styrene 100-42-5 17.39

Toxic Substances Control Act:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

Chemical NameCAS-No.1,6 hexandiol glycidyl ether16096-31-4

U.S. Clean Air Act:

EPA Coating Category: Industrial Maintenance Coatings

EPA VOC Content Limit (g/l): 450
Product VOC Content (g/l) 8
Thinning Recommendations: None

Application Recommendations: For professional use only.

U.S. State Regulations: As follows -

New Jersey Right-to-Know:

The following materials are non-hazardous, but are among the top five components in this product.

Chemical NameCAS-No.glass oxide65997-17-3

Pennsylvania Right-To-Know

The following non-hazardous ingredients are present in the product at greater than 3%.

Chemical NameCAS-No.glass oxide65997-17-3

California Proposition 65:

^{*} As per the federal EPA definition for coating categories in 40 CFR 59.401.

^{**} Grams of VOC per liter of coating product as applied (mixture of Part A and Part B) per ASTM D2369 Method E.

WARNING: Cancer - www.P65Warnings.ca.gov

WARNING: Reproductive Toxicant -- www.P65Warnings.ca.gov

International Regulations: As follows -

* Canadian DSL:

All chemical ingredients included on inventory or exempt.

15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

16. Other Information

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H340	May cause genetic defects.
H350	May cause cancer.
H351	Suspected of causing cancer.
H361d	Suspected of damaging the unborn child.
H370	Causes damage to organs

H370 Causes damage to organs.

H372 Causes damage to organs through prolonged or repeated exposure.

Reasons for revision

Composition Information Changed

Substance and/or Product Properties Changed in Section(s):

- 01 Identification
- 02 Hazard Identification
- 03 Composition/Information On Ingredients
- 05 Fire-fighting Measures
- 08 Exposure Controls/Personal Protection
- ${\tt 09}$ Physical and Chemical Properties
- 11 Toxicological Information
- 12 Ecological Information
- 14 Transportation Information
- 15 Regulatory Information

Revision Statement(s) Changed

List of References:

This Safety Data Sheet was compiled with data and information from the following sources:

- The Ariel Regulatory Database provided by the 3E Corporation in Copenhagen, Denmark.

- Joint Research Centre in Ispra, Italy.
- Regulation (EC) 1272/2008 with subsequent amendments.
- Regulation (EC) 1272/2006 with subsequent amendments.
- Commission Regulation (EU) 2020/878
- EU Council Decision 2000/532/EC and its Annex entitled "List of Wastes"
- Safety Data Sheet from raw material supplier
- The classification of the product is based on the calculation methods set out in Annex I and Annex II of the CLP Reg. 1272/2008 on the exact composition of the formula

Acronym & Abbreviation Key:

CLP Classification, Labeling & Packaging Regulation

EC European Commission
EU European Union
US United States

CAS Chemical Abstract Service

EINECS European Inventory of Existing Chemical Substances

REACH Registration, Evaluation, Authorization of Chemicals Regulation

GHS Globally Harmonized System of Classification and Labeling of Chemicals

LTEL Long term exposure limit
STEL Short term exposure limit
OEL Occupational exposure limit

ppm Parts per million

mg/m3 Milligrams per cubic meter TLV Threshold Limit Value

ACGIH American Conference of Governmental Industrial Hygienists

OSHA Occupational Safety & Health Administration

PEL Permissible Exposure Limits
VOC Volatile organic compounds

g/l Grams per liter

mg/kg Milligrams per kilogram

N/A Not applicable LD50 Lethal dose at 50%

LC50 Lethal concentration at 50%

EC50 Half maximal effective concentration

IC50 Half maximal inhibitory concentration

PBT Persistent bioaccumulative toxic chemical

vPvB Very persistent and very bioaccumulative

EEC European Economic Community

ADR International Transport of Dangerous Goods by Road RID International Transport of Dangerous Goods by Rail

UN United Nations

IMDG International Maritime Dangerous Goods Code
IATA International Air Transport Association

MARPOL International Convention for the Prevention of Pollution From Ships, 1973 as

modified by the Protocol of 1978

IBC International Bulk Container
RTI Respiratory Tract Irritation

NE Narcotic Effects

IMO International Maritime Organization

Note P: The classification as a carcinogen or mutagen need not apply; the substance

contains less than 0,1 % w/w benzene

Note 10: The classification as a carcinogen by inhalation applies only to mixtures in

powder $% \left(1\right) =\left(1\right) +\left(1\right) +\left($

or incorporated in particles with aerodynamic diameter ≤ 10 µm.

For further information, please contact: Technical Services Department

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product or where instructions and recommendations are not followed.